

# MATERIAL SAFETY DATA SHEET

PAGE 1 OF 2

<b>IDENTITY</b>	<b>ReddyGo®</b>
-----------------	-----------------

## SECTION I

<b>MANUFACTURER:</b> A.L. WILSON CHEMICAL CO. 1050 HARRISON AVENUE P.O. BOX 207 KEARNY, NJ 07032	<b>EMERGENCY TELEPHONE NUMBER</b>	800-424-9300 or 703-527-3887
	<b>TELEPHONE NUMBER FOR INFORMATION:</b>	201-997-3300
	<b>DATE PREPARED:</b>	January 1, 2007

## SECTION II - IMPORTANT INGREDIENTS / IDENTITY INFORMATION

IMPORTANT COMPONENTS	CHEMICAL IDENTITY	CAS #	%	TLV
ETHANOL 2-(-2BUTOXY-ETHOXY)	C <sub>4</sub> H <sub>9</sub> O (C <sub>2</sub> H <sub>4</sub> O) <sub>2</sub> H	112-34-5		ND
METHYL ISOAMYL KETONE	C <sub>7</sub> H <sub>14</sub> O	110-12-3		50 PPM ACGIH
TRICHLOROETHYLENE *	CHCl=CCl <sub>2</sub>	79-01-06	approx. 25	OSHA 100 PPM 8 Hr TWA
NONYLPHENOL ETHOXYLATE		9016-45-9		ND
2 ETHOXYL ETHANOL *	C <sub>2</sub> H <sub>5</sub> OC <sub>2</sub> H <sub>4</sub> OH	110-80-5	< 5	5 PPM ACGIH

\* Subject to SARA, Title III, Section 313 and 40 CFR 372.

## SECTION III - PHYSICAL / CHEMICAL CHARACTERISTICS

<b>BOILING POINT</b>	ND	<b>SPECIFIC GRAVITY (H<sub>2</sub>O=1)</b>	approx. 1.06
<b>VAPOR PRESSURE (mm Hg)</b>	ND	<b>MELTING POINT</b>	NA
<b>VAPOR DENSITY (air =1)</b>	ND	<b>EVAPORATION RATE (butyl acetate =1)</b>	ND
<b>SOLUBILITY IN WATER</b>	highly soluble		
<b>APPEARANCE AND ODOR</b>	light yellow to light amber with slightly sweet odor		

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

WARNING: Flammable Liquid and Vapor. Keep away from heat, sparks and flame.	
<b>FLASH POINT</b>	<b>FLAMMABLE LIMITS</b>
greater than 115° F.	ND
(method used)	
T.C.C.	
<b>EXTINGUISHING MEDIA</b> water, carbon dioxide "CO <sub>2</sub> ", dry chemical or foam	
<b>SPECIAL FIRE FIGHTING PROCEDURES</b> ND	
<b>UNUSUAL FIRE AND EXPLOSION HAZARDS</b> ND	

NA = Not Applicable  
 ND = Not Determined

See Page 2 for more information.

**SECTION V - REACTIVITY DATA**

<b>STABILITY</b> stable	<b>CONDITIONS TO AVOID</b> heat, sparks, open flame.
<b>INCOMPATIBILITY (MATERIALS TO AVOID)</b> none known	
<b>HAZARDOUS DECOMPOSITION PRODUCTS</b> hydrogen chloride, carbon monoxide, phosgene in small amounts	
<b>HAZARDOUS POLYMERIZATION</b> will not occur	

**SECTION VI - HEALTH HAZARD DATA****EFFECTS OF OVEREXPOSURE**

**EYES:** Liquid can be severely irritating to eyes.

**SKIN:** Liquid is moderately irritating to the skin. Prolonged or repeated contact can result in defatting and drying of skin, and dermatitis.

**INGESTION:** May cause headache, nausea, vomiting, breathing difficulty, weakness.

**INHALATION:** Overexposure may cause irritation or dryness of nose or throat or may cause drowsiness.

**FIRST AID**

**EYES:** Immediately flush thoroughly with water for 15 minutes. Get medical attention as soon as possible.

**SKIN:** Immediately flush thoroughly with water. Remove contaminated clothes.

**INGESTION:** See a physician as soon as possible.

**INHALATION:** Remove victim to fresh air.

**SECTION VII - PRECAUTIONS FOR SAFE HANDLING AND USE****STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED**

Extinguish all ignition sources. Absorb liquid with paper, vermiculite, floor absorbent or other absorbent materials. See below.

**WASTE DISPOSAL METHOD**

Dispose of in accordance with federal, state and local regulations.

**PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING**

Keep in cool ventilated place.

**SECTION VIII - CONTROL MEASURES****RESPIRATORY PROTECTION**

None needed when used with adequate ventilation.

**VENTILATION**

Use in adequately ventilated area.

**PROTECTIVE GLOVES**

neoprene or PVA coated

**EYE PROTECTION**

chemical splash goggles

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT**

rubber apron

**WORK/HYGIENIC PRACTICES**

Wash thoroughly after handling. Do not smoke, eat or drink in work area.