



A.L. WILSON CHEMICAL CO.

STAIN REMOVAL SPECIALTIES SINCE 1928

P.O. BOX 207 • 1050 HARRISON AVENUE • KEARNY, NEW JERSEY 07032

PHONE: (800) 526-1188 • (201) 997-3300 • FAX: (201) 997-5122

EMAIL: Help@ALWilson.com

Stain Removal Tips

- 1) Always use appropriate Personal Protection Equipment (gloves, safety glasses, etc.) Maintain adequate ventilation.
- 2) Maintain a clean work area with good lighting.
- 3) Most stains can be removed through skillful spotting, but some stains cannot be completely removed. The more you know, the better your chances for success!
- 4) Read all Material Safety Data Sheets carefully.
- 5) Read the directions for your stain removers in order to maximize the usefulness of the products.
- 6) Read garment care labels before starting.
- 7) Make sure your spotting bottles are correctly labeled (product ID, hazmat warnings, etc.)
- 8) Never put a chemical in a bottle that is labeled for another.
- 9) Test for colorfastness before applying stain removers.
- 10) Do not mix dryside and wetside stain removers. Use a black spotting brush for dryside stain removers and a white spotting brush for wetside stain removers.
- 11) On tough stains, give stain removers time to work.
- 12) Keep steam gun four inches from fabric, at a 90° angle to the fabric surface.
- 13) Completely flush stain removers from fabric. Let fabric dry thoroughly before drycleaning.
- 14) Neutralize alkali-related color changes with tannin formula or rust remover. Neutralize acid-related color changes with protein formula.
- 15) Do not use rust remover containing Hydrofluoric Acid on metallic, glass or fiberglass fabric or trim, or on Do-Not-Use-Chlorine-Bleach fabric.
- 16) Do not use acetone or acetic acid on acetate. In addition, be cautious when using heat on acetate.
- 17) Sugar stains may be invisible at first, but may caramelize or turn brown with heat or age.